

**DESCRIPTION**

Total thickness	EN 428	mm	1.5 * / 2.0
Weight	EN 430	g/m <sup>2</sup>	2500 / 3300
Width of sheet	EN 426	cm	200
Length of sheet	EN 426	lm	20






**CLASSIFICATION**

Norm / Product specification	-	-	EN 685
European classification	EN 649	class	23 - 31 / 34 - 43
K rating	-	class	K4
Fire rating	EN 13 501-1	class	Bfl-s1
	DIN 4102	-	B1
	GB 8624-2006	-	GB 8624 Bf1-s1
Toxic testing	GB 18586-2001	-	OK
Static electrical propensity	EN 1815	KV	< 2
Electrical resistance	EN 1081	Ω	10 <sup>9</sup> - 10 <sup>10</sup>
Slip resistance dry	pr EN 13893	-	≥0.3
Slip resistance wet	DIN 51 130	class	R9

**PERFORMANCE**

Abrasion resistance	EN 660.1	mm	≤0.18
Abrasion group	EN 649	group	M
Dimensional stability	EN 434	%	Sheet ≤ 0.4
Residual indentation	EN 433	mm	0.05
Thermal conductivity	EN 12 524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Chemical products resistance	EN 423	-	OK
Anti-bacterial and fungicidal	-	-	OK
Special maintenance treatment	-	-	PU
Color number	-	-	12

**CE MARKING 标识**

	EN 14041	 抗静电	 防火	 供地下暖气设备使用	 防滑
---	----------	---	--	---	--

\* Special order